



Thermostat Part Number Key/Variation Chart

Our Designation of Type-Code

X * I II III IV V VI - Open / Close

- X** = Type No., Basic Models
- *** = Electrical Rating & Contact Point
- I** = Switch Action on temperature Rise
- II** = Body Material (Automatic Only)
- VI** = Bracket, Mounting Arrangement
- IV+V** = Terminals
- III** = Sensing Cap

| | | | | | | | | | | | |
|----------------------------|---|---|---------------------------------|--------------------------------|------------------------------------|------------------------------------|------------------------------------|--------------------------------|----------------------------|--------------------------------|------|
| * | N AC 120V/AC 240V 15A/10A : Standard Contact Point | LICO Electronics GmbH Klederinger Str. 31 A-2320 Kledering, Austria office@lico.at www.lico.at Tel. +43 1 706 43 00 | | | | | | | | | |
| | C or S AC 120V/AC 250V 6A/3A : Conical Contact Point | | | | | | | | | | |
| | P AC 120V/DC6-30V 10M-100mA : Cross-Bar Contact Point | | | | | | | | | | |
| I | 1 Open on rise (operation type A) | | | | | | | | | | |
| | 3 Close on rise (operation type B) | | | | | | | | | | |
| II | 1 Phenolic | | | | | | | | | | |
| | 2 Ceramic | | | | | | | | | | |
| | 5 Phenolic (Euro Structure) | | | | | | | | | | |
| | 6 Polyester | | | | | | | | | | |
| III | 0,1,4,T,W Aluminum | No.0 | No.1,2,3 | No.4,5 | No.6 | No.7 | No.A,Y | No.R | No.S | No.T,U,V | No.W |
| | 2,7,S,U Copper Alloy | | | | | | | | | | |
| | 3,5,6,A,R,V Stainless Steel | | | | | | | | | | |
| | 0,1,2,3,A,R,W Fits w/Bracket#... | | | | | | | | | | |
| | 0 Open Cap | | | | | | | | | | |
| | T,U,V Close On Rise (Operation Type B) | No.0+5 Fixed Bracket | | | | | No.1+5, 2+5, 3+5 Fixed Bracket | | | | |
| | S Screw Threads (ISO,UNC) | | | | | | | | | | |
| 7,P,R Tube Mounting | | | | | | | | | | | |
| IV-V | No.01 Solder | | No.02 Solder | | No.05 .187 Quick Connect | | No.06/10 .187 Quick Connect | | No.07 Strap | | |
| | No.08 Weld | | No.11 Strap | | No.12 Crimp | | No.14 .187 Quick Connect | | No.61 Weld | | |
| | No.28 Strap | | No.36 .187 Quick Connect | | No.03/23 .250 Quick Connect | | No.04/24 .250 Quick Connect | | No.09/29 30° or 45° | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| VI | 0 No Bracket | | No. 1 | | No. 2 | | No. 3 | | No. 4 | No. H (Fits with Cap W) | |
| | B,H Fixed Bracket | | | | | | | | | | |
| | 1,2,3,4,A Loose Bracket | No. A | | No. B (Fits with Cap A) | | No. E,J,K (Fits with Cap R) | | No. L (Fits with Cap R) | | | |
| | A (With Spring) Tube Mounting | | | | | | | | | | |
| | E,J,K,L (With Cap R) Tube Mounting (3/8" 4/8" 5/8" 6/8" 7/8") | | | | | | | | | | |



NIPPON GT CORPORATION

3-12-15 Meguro-honcho, Meguro-ku, Tokyo 152-0002, Japan
Telephone +81-(0)3-3713-7124 Facsimile +81-(0)3-3794-0585